


iDS-2PT9122IX-DE/S (5-50 mm) (4 mm) PanoVu PT Series 2MP + 2MP Target Capture Camera



Hikvision iDS-2PT9122IX-DE/S (5-50 mm) (4 mm) PanoVu PT Series 2MP + 2MP Target Capture Camera is able to capture distant view images as well as close-up images with the integration design of distant view camera and tracking PTZ camera.

This series of camera can be widely used in the scenes where wide monitoring range and high definition are required, such as the entrance/exit, airport, port, wharf, reservoir, square, park, scenic spot, and station, etc.

Distant View Camera

- 1/2.7" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Horizontal field of view: 92°
- Min. illumination:
Color: 0.002 Lux@(F1.0, AGC ON),
B/W: 0.0005 Lux@(F1.0, AGC ON)

Tracking PTZ Camera

- 1/2.7" progressive scan CMOS
- Up to 1920 × 1080 resolution
- Horizontal field of view: 61.3° to 6.26°
- Pan and tilt range: 210° (Pan), -22° to 22° (Tilt)
- Min. illumination:
Color: 0.0035 Lux@(F1.6, AGC ON)
0 Lux with IR
- 10× optical zoom, 16× digital zoom



Specification


System	
One-touch Link	Support
Multiple Targets Tracking	Support
Calibration Mode	Auto/Manual
Target Switch Time	<1 s
Calibration	Manual/Auto
Smart Detection	Detects human body, face, and vehicle automatically.
Tracking Time Settings	Support
Distant View Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.002 Lux@(F1.0, AGC ON), B/W: 0.0005 Lux@(F1.0, AGC ON)
Focal Length	4.0 mm
Aperture	F1.0
Horizontal FOV	92°
S/N Ratio	>52 dB
3D DNR	Support
Smart Image Enhancement	Digital WDR, Defog, HLC, EIS, BLC
Basic Event Detection	Motion Detection, Video Tampering Detection, Alarm Input, Alarm Output, HDD Full, HDD Error, Network Disconnected, IP Address Conflicted, Illegal Login
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG
Main Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream Resolution	50Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Tracking PTZ Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.0035 Lux@(F1.6, AGC ON), 0 Lux with IR
S/N Ratio	>55 dB
3D DNR	Support
IR	IR distance: 100 m; IR brightness and angle are adjustable.
Smart Image Enhancement	Digital WDR, Defog, HLC, EIS, Smart IR, BLC
Focal Length	5 mm to 50 mm, 10× optical zoom
Zoom Speed	Approx.2.5 s (Optical Wide-Tele)
Horizontal FOV	61.3° to 6.26° (Wide-Tele)
Min. Working Distance	10 mm to 1500 mm (Wide-Tele)
Aperture Range	F1.6 to F3.0
Pan and Tilt Range	Pan: 210°, Tilt: -22° to 22°
Pan and Tilt Speed	Pan Manual Speed: 0.1°/s to 200°/s (Configurable), Pan Preset Speed: 300°/s Tilt Manual Speed: 0.1°/s to 120°/s (Configurable), Tilt Preset Speed: 120°/s
Preset Number	300
Patrol	8 patrols, up to 32 presets per patrol
Park Action	Preset/Patrol Scan
Scheduled Task	Preset/Patrol Scan/Dome Reboot/Dome Adjust/Aux Output
Power-off Memory	Support
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG

Main Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream Resolution	50Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream Resolution	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Audio Compression	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM
Network	
Protocols	TCP/IP, IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
API	Open-ended, support ONVIF, ISAPI, and CGI, support HIKVISION SDK and Third-Party Management Platform
Network Storage	Built-in memory card slot, support Micro SD/SDHC/SDXC (up to 256 GB)
Web Browser	IE 8 to 11, Firefox 32.0.1, 38.0, 43.0.1, Chrome 40.0.2214.94
Interface	
Network Interface	1 RJ45 10 M/100 M Ethernet Interface, Hi-PoE
Alarm Input/ Output	1-ch alarm input and 1-ch alarm output, support alarm linkage: Memory Card Recording/Aux Output/Notify Surveillance Center/Upload to FTP/Send Email
Audio Input/ Output	1-ch audio input and 1-ch audio output
General	
Power Supply	12 VDC & Hi-PoE
Power Consumption	45 W Max. (IR 6 W Max.)
Working Temperature	Outdoor: -40°C to 70°C (-40°F to 158°F)
Working Humidity	≤ 90%
Protection Level	IP66 Standard, TVS 6000 V Lightning Protection, Surge Protection and Voltage Transient Protection
Dimension	195.1 mm × 280.8 mm × 174.8 mm (7.68" × 11.06" × 6.88")
Weight	Approx. 2.5 kg (5.51 lb)

Available Model

iDS-2PT9122IX-DE/S (5-50 mm) (4 mm), 12 VDC & Hi-PoE

Dimension



Accessories



DS-2601ZJ-P
Wall Mounting Bracket

Note:

DS-2601ZJ-P is included. And you should purchase DS-2115ZJ-P in addition. The diameter of the hold hoop is 67 mm to 127 mm.



DS-2665ZJ-P
Base Mounting Bracket

Note:

DS-2665ZJ-P is not included. And you should purchase DS-2115ZJ-P in addition. The diameter of the hold hoop is 67 mm to 127 mm.

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Hong Kong
T +852-2151-1761