

# IR FIXED LENS VANDAL-PROOF MINI DOME CAMERA

DMA-390IP528



1/2.7" CMOS Sensor  
2 Mega-Pixel  
True Day & Night (IR Cut Removable)  
H.265 (HEVC) Compression  
0 Lux (IR On) Min. Illumination

ONVIF  
True WDR / BLC / HLC  
3D Noise Reduction  
Motion Detection and Privacy Masking  
Analytics Support

2.8mm Mega-Pixel Lens  
10m IR Illumination  
PoE Support  
1 Way Audio  
Local Storage

1 Way Audio  
Built-In Microphone  
CVBS  
IP 66 Protection  
IK 10 Vandal Proof

## Specifications

Camera	Video	Model	DMA-390IP528
		Image Sensor	1/2.7" CMOS (16:9)
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	1-25/30FPS
		Day & Night	ICR
		Min. Illumination	Day: 0.022lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
Motion Detection		Yes	
Compression	Analytics	Camera Tampering, Line Crossing, Sterile Area	
	Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)	
	Resolution	1080P (1920x1080), 720P (1280x720), D1, CIF	
	Multi-Stream	1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS)	
	Bit rate	64Kbps ~ 4Mbps@H.265 / 128Kbps ~ 6Mbps@H.264	
Encode Mode	VBR/CBR		
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	10m (12 IR LED)
	Lens (Field of View)	2.8mm (101.7°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66 / Vandal Proof: IK10
	Bracket	3-Axis Gimbal
Connectivity	Dimensions	Φ110mm×57.8mm
	Weight(gross)	350g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Audio Connectivity	Built-In Microphone + Mic Input
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)
	RS485	No
	Alarm	No
	Network	Remote Monitoring
User Access		Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Network Protocol		TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS
ONVIF		Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	DC12V/~340mA / PoE/~4.7W	
Work Environment	-30 C~50 C, 10%~90% Humidity	

