


# 80M IR MOTORIZED VF BULLET CAMERA

I8-340IP5MVF+



1/3" CMOS Sensor  
4 Mega-Pixel  
True Day & Night (IR Cut Removable)  
H.265 (HEVC) Compression  
0 Lux (IR On) Min. Illumination

ONVIF  
True WDR / BLC / HLC  
3D Noise Reduction  
Motion Detection and Privacy Masking  
9-22mm Motorized Lens with Auto-Focus

80m IR Illumination  
PoE Support  
Local Storage  
RS-485  
I/O – 1 Alarm in / 1 Alarm Out

2 Way Audio  
CVBS  
Technician Port  
IP 66 Protection

## Specifications

|                  |  |  |  |
|------------------|--|--|--|
| Camera           | Video  | Model  | I8-340IP5MVF+  |
|                  |  | Image Sensor   | 1/3" CMOS  |
|                  |  | Effective Pixels   | 2688x1520  |
|                  |  | Electronic Shutter   | 1/25s ~ 1/100000s  |
|                  |  | Frame Rate   | 1-25/30 (With True-WDR)  |
|                  |  | Day & Night  | ICR  |
|                  |  | Min. Illumination  | 0lux (IR ON)   |
|                  | Audio  | Audio compression  | G.711A/G.711U  |
|                  |  | Communication  | Two-Way Audio  |
|                  | Image Enhancement                                | Image Settings   | AWB, AGC Adjustable<br>Exposure Mode (Auto)<br>Sharpness, Saturation, Brightness & Contrast Adjustable |
|                  |  | Image Enhancement  | True WDR / BLC / HLC / ROI   |
|                  |  | Noise Reduction  | 3D-DNR   |
|                  |  | Image Orientation  | Mirror/Flip  |
|                  |  | Privacy Zone   | Yes  |
| Motion Detection |  | Yes  |  |
| Compression      | Video Compression                                | H.265 / H.264  |  |
|                  | Resolution                                       | 4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240      |  |
|                  | Multi-stream                                     | 4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS) |  |
|                  | Bit rate   | 64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264                       |  |
|                  | Encode Mode                                      | VBR/CBR  |  |
| Image Quality    | Five levels under VBR; Free adjustment under CBR |  |  |

|              |                     |   |
|--------------|---------------------|---|
| Housing      | IR Distance         | 80m (4 IR LED Array)  |
|              | Lens                | 9-22mm Motorized with Auto-Focus  |
|              | Iris                | Fixed Iris  |
|              | Lens Mount          | Φ14 mount   |
|              | Protection Rate     | Water Proof: IP66   |
|              | Bracket             | 3-Axis  |
|              | Dimensions          | Φ109mm×284mm  |
| Connectivity | Weight(gross)       | 1700g   |
|              | Network             | RJ45 (+PoE)   |
|              | Power               | DC Socket   |
|              | Analog Video Output | CVBS(BNCx1)   |
|              | Mic Connectivity    | 1Ch Input, 1Ch Output   |
|              | SD Card             | Support Event Recording over SD (128GB Max)   |
|              | RS485               | Yes   |
| Network      | Alarm               | 1Ch Input, 1Ch Output   |
|              | Remote Monitoring   | IE Browsing, CMS Software, Provision Cam2 Mobile App  |
|              | User Access         | Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission |
|              | Network Protocol    | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP                                  |
|              | ONVIF               | Yes   |
|              | Ethernet            | 100Mbps   |
|              | PoE                 | Yes   |
| Others       | Power Supply        | DC12V/~980mA / PoE/~14W   |
|              | Work Environment    | -30 C ~50 C, 10%~90% Humidity   |

