

# IC-PPH



**Polo standard white phone**

**Application:**

Used in a house along with Entry panel unit for exterior comms.

**Key Features:**

- Only 2 wires
- 12V DC operating voltage
- Expand up to 5 components in the system.
- Convenient intercommunication between 2 groups of handsets
- Auxiliary push-button on each handset.



<b><u>TECHNICAL SPECIFICATIONS</u></b>		
OPERATING VOLTAGE	12-14V <sub>DC</sub> supplied from gate motor	
CURRENT DRAW	Quiescent	150mA (+60mA for 1:1 sys)
	Maximum	200mA
SPEECH VOLUME	Adjustable at each entry panel and handset	
WIRING	2 Common wires polarized for speech, call & lock.	
RING TONE	Electronic while button is depressed with separate tones when calling from each panel in a system or between groups of handsets.	
CALL CONFIRMATION AT ENTRY PANEL	Yes	
WIRING DISTANCE	Refer to thickness chart below.	
GATE/DOOR RELEASE	Potentially free normally open contact at entry panel. Door lock requires separate power supply.	

HANDSET AUXILIARY CONTACT	Potentially free normally open contact. Requires separate wiring to 2-Wire bus.
OPERATING TEMP	-20°C to +50°C
HUMIDITY	0-90% non condensing
IP RATING	IP56
SURGE PROTECTION	Yes

