



E-LOCK MAGNETIC LOCKS INDOOR



LOC-ML1, LOC-ML1BR, LOC-ML3L, LOC-ML3BR, LOC,ML6 & LOC-ML6BR

TECHNICAL SPECIFICATIONS

LOC-ML1 (150KG Magnetic Indoor)	
	<ul style="list-style-type: none">• 150Kgs holding force• Operating voltage 12VDC• Current draw 300mA / 150mA• MOV surge protection• Fail-safe type• Unmonitored model• CE approved• Dimensions: 170mm x 36mm x 24mm
LOC-ML1BR (150KG ZL-Bracket)	
	<ul style="list-style-type: none">• For use with SP 150Kg Maglock (LOC-ML1)

LOC-ML3L (300KG Magnetic Indoor)	
	<ul style="list-style-type: none"> • 300Kgs holding force • Dual voltage 12 & 24VDC • Current draw 500mA / 250mA • MOV surge protection • Fail-safe type • Monitored (with LED, Hall effect IC & NO/NC relay) • CE approved • Dimensions:250mm x 41mm x 26mm
LOC-ML3BR (300KG ZL-Bracket)	
	<ul style="list-style-type: none"> • For use with SP 300Kg Maglock (LOC-ML3L)
LOC-ML6 (600KG Magnetic Indoor)	
	<ul style="list-style-type: none"> • 600Kgs holding force • Dual voltage 12 & 24VDC • Current draw 500mA / 250mA • MOV surge protection • Fail-safe type • Monitored (with LED, Hall effect IC & NO/NC relay) • CE approved • Dimensions:265mm x 66mm x 20mm
LOC-ML6BR (600KG ZL-Bracket)	
	<ul style="list-style-type: none"> • For use with SP 600Kg Maglock (LOC-ML6)