

2 Monitor Professional High Performance Remote Monitoring Workstation

The innovative Avigilon™ hardware solutions portfolio provides a secure, reliable, and scalable platform from small sites and large systems. Our high-performance HD remote monitoring workstation enables you to add to an existing Avigilon system for superior monitoring and protection.



The professional high performance remote monitoring workstations are designed to achieve the highest performance for a client workstation within an Avigilon HD Surveillance System. Pre-loaded with Avigilon Control Center™ Client software, the remote monitoring workstation is easily installed to accompany NVR products and to add an additional monitoring station to existing systems, with support for two high resolution monitors* and up to a total of 72 video streams.

KEY FEATURES

- Preloaded with Avigilon Control Center High Definition Network Video Management Client Software
- Supports up to two high resolution monitors*
- Supports viewing up to 72 video streams simultaneously
- Desktop form factor
- Video adapters, keyboard and mouse included

*Monitor sold separately

Specifications

SYSTEM	Viewing Streams	Up to 72
	Operating System	Microsoft® Windows 10 Enterprise
	Processor	6th Gen Intel® Core™ i5-6600
	Memory	8 GB DDR4 RAM
	Network Interface	2 Gigabit Ethernet RJ-45 ports (1000Base-T)
	Video Outputs	2 Active (1 DisplayPort and 1 DVI-I)
	Optical Drive	DVD-RW
	Supported Monitor Interfaces	Up to 2 combinations of DP, DVI and/or HDMI (with supplied accessories)

MECHANICAL	Form Factor	Desktop
	Dimensions (WxHxD)	175 mm x 360 mm x 435 mm; 6.89" x 14.17" x 17.12"
	Weight	9.24 kg (20.35 lbs)

ELECTRICAL	Power Input	100 to 240 VAC, 50/60 Hz, auto-switching
	Power Supply	Single non-redundant
	Power Consumption	290 W

ENVIRONMENTAL	Operating Temperature	5° C to 35° C (41° F to 95° F)
	Storage Temperature	-40° C to 65° C (-40° F to 149° F)
	Humidity	20% to 80% relative humidity (non-condensing)
	Operating Vibration	0.26 GRMS
	Storage Vibration	2.20 GRMS
	Operating Shock	Shock pulse of 40G for up to 2 ms
	Storage Shock	Shock pulse of 105G for up to 2 ms
	Operating Altitude	-15.2 m to 3048 m (-50 ft to 10,000 ft)
Storage Altitude	-15.2 m to 10,668 m (-50 ft to 35,000 ft)	

SUPPLIED ACCESSORIES	USB Keyboard
	USB Mouse
	Power cord
	2 DVI to HDMI adapters
	1 DisplayPort to DVI adapter

CERTIFICATIONS	Certifications/Directives	UL	cUL	CE	RCM
		CCC	EAC	VCCI	KC
		BSMI	NRCS	RoHS	SVHC

ORDERING INFORMATION	HD-RMWS3-2MN	Avigilon Control Center Professional high performance remote monitoring workstation for up to 2 monitors*
		* Monitor sold separately

