

# RB260GS



The RB260GS is a small SOHO switch. It has five Gigabit Ethernet ports and one SFP cage powered by an Atheros Switch Chip.

It is powered by an operating system designed specifically for MikroTik Switch products - SwOS.

SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: Allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.

- Smart switch
- Small and compact
- Plastic case
- Five Gigabit ports
- Web interface controlled
- Smarter than smart



CPU	Taifatech TF470
Memory	Embedded 96K SRAM
Ethernet	Five 10/100/1000 Ethernet ports, Atheros switch AR8327 One fixed Gigabit Ethernet SFP cage (Mini-GBIC; SFP module not included)
Serial port	No serial port
LEDs	Power, NAND activity, 5 Ethernet activity LEDs
Extras	Hardware watchdog
Power options	PoE: 8-30V DC on Ether1 (Non 802.3af). Jack: 8-30V DC
Dimensions	113x89x28mm. Weight without packaging and cables: 142g
Power consumption	Up to 6W
Operating Temperature	-25C .. +65C
Operating System	MikroTik SwOS

