


# BOUNDARY OUTDOOR DETECTOR BX SHIELD series



When superior performance  
meets modern design



The BX Shield is a series of outdoor  
PIRs providing 12m per side  
curtain coverage:

**Black and white models**

BXS-ST: 12 m / 40 ft side by side (total 24 m / 80 ft)

BXS-AM: with anti-masking

BXS-R: Battery operated 12 m / 40 ft side by side (total 24 m / 80 ft)

BXS-RAM: with anti-masking

**White models**


BXS-ST (W)

BXS-AM (W)

BXS-R (W)

BXS-RAM (W)






# SHIELD: the new shape of security

4 PIR SENSORS, IR DIGITAL ANTI-MASKING AND SHIELD CONCEPT DESIGN




## Reliable

Up to 12m/ 40ft. flexible detection areas on each side of the sensor




### AND logic function to reduce false alarms

The BX SHIELD only triggers an alarm signal when both upper and lower areas detect movement.




### Individual detection area and sensitivity setting

Both left and right detection ranges can be independently adjusted. (2.5 to 12 m in 5 steps)



### Extreme high detection mode

For environments where the temperature difference between the human body and the background is very small, the extreme high detection mode increases the PIR sensitivity to prevent any missed alarms.



Normal			Extreme		
Normal Low	Normal Mid	Normal High	Extreme Low	Extreme Mid	Extreme High


### SMDA (Super Multidimensional Analysis) logic

All BX SHIELD models feature a digitally enhanced signal recognition logic called SMDA increasing detection reliability. By analysing the detection patterns and environmental information SMDA can differentiate between genuine intrusions and a number of noise factors such as changes in weather conditions and swaying vegetation.




### 4 PIR technology

The detection range, sensitivity and alarm output can be set separately for the left and right detection areas. The sensor can differentiate between large and small objects within the detection area, reducing false activations and ensuring genuine intruder detection.



### IR digital anti-masking function

Active IR anti-masking detects when the lens surface has been covered, blocked or painted.




### Individual signal outputs (left and right)

The BX SHIELD triggers independent alarm outputs for the left and the right detection areas which is useful when connected to PTZ cameras.





# Convenient



90 degrees rotation mechanism  
Easy to open / close cover



Level indicator  
The BX SHIELD series features a level indicator to ease the installation process.

## Blue Touch™




All the components needed for the sensor's adjustment and settings are in blue for ease of installation.



Easy to adjust detection angle

## Automatic walk test mode

Walk test mode will time out after three minutes and the setting will return to "normal mode".



# Secure

A sense of security, designed for you



Flat profile supported  
by an internal honeycomb structure ensures durability.



Optional colours for faceplate covers allow for more discrete installations.



Optical lens units are sealed and re-enforced to add extra strength.

## Back tamper

Tamper output activates when face cover or back box is removed.



## Product Features


### Battery life for the battery-operated models

Model	BXS-R		BXS-RAM		
	Interval (sec.)	120	5	120	5
Approx. years	5	3.5	5	3.5	
	3	2	3	2	
	4	2.5	4	2.5	


Battery type
CR123A (3 V DC, 1300 mAh)
CR2 (3 V DC, 750 mAh)
1/2 AA (3 V DC, 1000 mAh)

Calculations based on ;  
Single type battery, no power sharing with transmitter, LED OFF and Anti-masking ON.

Wireless transmitter and battery



Battery box RBB-01 (option)



Battery box (RBB-01)



\*Battery not included.  
CR123A x 3 (3.0 V DC)  
CR2 x 3 (3.0 V DC)  
1/2AA x 3 (3.6 V DC)  
1/2AA x 6 (7.2 V DC x 3)\*  
\*3.6 V DC 1/2 AA battery in series.

### EOL module socket (BXS-ST,AM only)

Optional EOL (End of line) resistor modules are available.

### SHIELD housing

IP55 protection  
UV resistant ASA body




IP55



UV protection

### Pole mount plate (option)



Suitable for a metal band up to 23 mm (1 inch) in width

### Versatile design



Black cover / black body



White cover / black body



Silver cover / black body



White cover / white body



Web based manual for wired models

<http://navi.optex.net/manual/50155>



Web based manual for battery operated models

<http://navi.optex.net/manual/50157>




Basic common features

• Double conductive shielding  
• Cover tamper


• Sensitivity adjustment switch

## Coverage

Top view



Side view




Unit: m (ft.)


## Dimensions

BXS-ST / BXS-AM

Unit: mm (inch)



BXS-R / BXS-RAM



## Options

PLUG-IN EOL (PEU)



BXS Face cover (White / Silver / Black)

BXS Back box (White / Black)

BXS Back box Cap (White / Silver / Black)

BXS Pole mount plate

BATTERY BOX (RBB-01)



Metal band: 23 mm or less in width

## Specifications

Model	BXS-ST	BXS-AM	BXS-R	BXS-RAM
Detection method	Passive infrared		Passive infrared	
Coverage	24 m (80') ; 12 m (40') on each side, 4 zones ; 2 zones on each side, 180° narrow		24 m (80') ; 12 m (40') on each side, 4 zones ; 2 zones on each side, 180° narrow	
PIR distance settings	2.5, 3.5, 6, 8.5, 12 m		2.5, 3.5, 6, 8.5, 12 m	
Detection angle from wall	TO WALL : 0° angled forward AWAY WALL : 3° angled forward selectable		TO WALL : 0° angled forward AWAY WALL : 3° angled forward selectable	
Detectable speed	0.3 to 2.0 m/s (1' to 6'7"/s)		0.3 to 2.0 m/s (1' to 6'7"/s)	
Sensitivity	Normal ; 2.0°C (3.6°F) at 0.6 m/s Extreme high : 1.0°C (1.8°F) at 0.6 m/s selectable for each side individually		Normal ; 2.0°C (3.6°F) at 0.6 m/s Extreme high : 1.0°C (1.8°F) at 0.6 m/s selectable for each side individually	
Power input	9.5 to 18 V DC		3 to 9 V DC Lithium or Alkaline batteries	
Current draw (except walk test)	31 mA max. at 12 V DC	34 mA max. at 12 V DC	15 µA stand-by / 8 mA max. at 3 V DC	16 µA stand-by / 8 mA max. at 3 V DC
Alarm period	2.0 ± 1 sec.		2.0 ± 1 sec.	
Warm-up period	60 sec. or less (LED blinks)		60 sec. or less (LED blinks)	
Alarm output (R)	28 V DC 0.1 A max. [Individual; Right or General], [N.O. or N.C.] are selectable		Solidstate switch, 10 V DC 0.01 A max. [Individual; Right or General], [N.O. or N.C.] are selectable	
Alarm output (L)	28 V DC 0.1 A max. [Individual; Left or General], [N.O. or N.C.] are selectable		Solidstate switch, 10 V DC 0.01 A max. [Individual; Left or General], [N.O. or N.C.] are selectable	
Trouble output	-	N.C. 28 V DC 0.1 A max.	Solidstate switch, 10 V DC 0.01 A max. [N.O. or N.C.] is selectable	
Tamper output	N.C. 28 V DC 0.1 A max. open when face cover, main unit or base unit is removed		Tamper output is shared with trouble output.	
LED indicator	Red LED ; 1. Warm-up 2. Alarm (DIP switch ON or Walk test)	Red LED ; 1. Warm-up 2. Alarm, 3. Masking detection (DIP switch ON or Walk test)	Red LED ; 1. Warm-up 2. Alarm (DIP switch ON or Walk test)	Red LED ; 1. Warm-up 2. Alarm, 3. Masking detection (DIP switch ON or Walk test)
Operation temperature	-30°C to +60°C (-22°F to +140°F)		-30°C to +60°C (-22°F to +140°F)	
Relative humidity	95% max.		95% max.	
International protection	IP 55		IP 55	
Mounting	Wall, pole (outdoor, indoor)		Wall, pole (outdoor, indoor)	
Mounting height	0.8 to 1.2 m (2'7" to 4')		0.8 to 1.2 m (2'7" to 4')	
Weight	430 g (15.2 oz.)		550 g (19.4 oz.)	
Accessories	Screw (4 x 20 mm) x 2		[1] Connector for POWER and ALARM (R), [2] Connector for ALARM (L), [3] Connector for TROUBLE, [4] Velcro tape, [5] Screw (4x20 mm) x 2	

\* Specifications and designs are subject to change without prior notice.

\* These units are designed to detect an intruder and activate an alarm control panel.

Being only a part of a complete system, we cannot accept responsibility for any damages or other consequences resulting from an intrusion.



OPTEX CO.,LTD. (JAPAN)

www.optex.net

OPTEX INC. / AMERICAS HQ (U.S.)  
www.optexamerica.com

OPTEX DO BRASIL LTDA. (Brazil)  
www.optex.net/br/es/sec

OPTEX (EUROPE) LTD. / EMEA HQ (U.K.)  
www.optex-europe.com

OPTEX TECHNOLOGIES B.V. (The Netherlands)  
www.optex.eu

OPTEX SECURITY SAS (France)  
www.optex-security.com

OPTEX SECURITY Sp.z o.o. (Poland)  
www.optex.com.pl

OPTEX PINNACLE INDIA, PVT., LTD. (India)  
www.optex.net/in/en/sec

OPTEX KOREA CO.,LTD. (Korea)  
www.optexkorea.com

OPTEX (DONGGUAN) CO.,LTD.  
SHANGHAI OFFICE (China)  
www.optexchina.com

OPTEX (Thailand) CO., LTD. (Thailand)  
www.optex.co.th