



8CH TURBO HD DVR WITH 2TB HDD

HLDVR-208U-K1



FEATURES AND FUNCTIONS

Video Input and Transmission

- Self-adaptive HDTV/HD/SD/Analog/CVBS signal input
- Up to 4-ch 6 MP IP cameras input for DVR-208U-K1
- 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5 MP/4 MP for DVR-204U-K1
- Defogging function enabled for the supported analog cameras
- Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal

Compression and Recording

- H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras
- Connectable to H.265+/H.265/H.264+/H.264 IP cameras
- H.265+ can be enabled to improve encoding efficiency and reduce data storage costs
- Full channel recording at up to 8 MP resolution

Video Output

- Simultaneous HDMI/VGA output
- HDMI output at up to 4K (3840 × 2160) resolution for DVR-208U-F1

Storage and Playback


- 1 SATA interface (up to 8 TB capacity per HDD)
- 4/8-ch synchronous playback
- Smart search for efficient playback
- Supports the 3rd party cloud storage (Dropbox/Google Drive/Microsoft OneDrive)

Smart Function

- Supports multiple VCA (Video Content Analytics) events for both analog and smart IP cameras
- Supports line crossing detection and intrusion detection of all channels, and 2-ch sudden scene change detection
- VCA information overlay in live view and smart playback
- VQD (Video Quality Diagnostics)
- Supports PTZ control via Omnicast VMS of Genetec protocol

Network & Ethernet Access

- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- 1 RJ45 10M/100M self-adaptive Ethernet interface for DVR-204U-K1, and 1 RJ45 10M/100M/1000M self-adaptive Ethernet interface for DVR-208U-K1
- Output bandwidth limit configurable



FIRE • SECURITY • INTERCOMS

17 Millicent Street, Burwood, VIC 3125 Australia

Tel: 1300 PSA PRODUCTS (1300 772 776)

Fax: (03) 9888 9993

enquiry@psaproducts.com.au

psaproducts.com.au





SPECIFICATIONS

Model

HLDVR-208U-K1

| Model | | HLDVR-208U-K1 | |
|--------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Video/Audio input | Video compression | H.265+/H.265/H.264+/H.264 | |
| | Analog video input | 8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection | |
| | HDTVl input | 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 | |
| | AHD input | 5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30 | |
| | HDCVl input | 4 MP, 1080p25, 1080p30, 720p25, 720p30 | |
| | CVBS input | PAL/NTSC | |
| | IP video input | 4-ch Up to 6 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras | |
| | Audio compression | G.711u | |
| Video/Audio output | HDMI/VGA output | VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | |
| | Encoding resolution | 8 MP/5 MP/4 MP/ 3 MP/1080p/720p/WD1/4CIF/VGA/CIF | |
| | Frame rate | Main stream: 8 MP@8fps/5 MP@12fps/4 MP@15fps/3 MP@18fps 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N) | |
| | Video bit rate | 32 Kbps to 10 Mbps | |
| | Audio output | 1-ch, RCA (Linear, 1 KΩ) | |
| | Audio bit rate | 64 Kbps | |
| | Dual stream | Support | |
| | Stream type | Video, Video & Audio | |
| | Synchronous playback | 8-ch | |
| | Network management | Remote connections | 64 |
| | | Network protocols | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF |



Model

HLDVR-208U-K1

| Hard disk | SATA | 1 SATA interface | |
|----------------------|---------------------------|---------------------------------------------------------|--|
| | Capacity | Up to 8 TB capacity for each disk | |
| External interface | Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input) | |
| | Network interface | 1, RJ45 10M/100M/1000M self-adaptive Ethernet interface | |
| | USB interface | 2 × USB 2.0 | |
| General | Power supply | 12 VDC | |
| | Consumption (without HDD) | ≤ 20 W | |
| | Working temperature | -10 °C to +55 °C (+14 °F to +131 °F) | |
| | Working humidity | 10% to 90% | |
| | Dimensions (W × D × H) | 315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch) | |
| Weight (without HDD) | ≤ 2 kg (4.4 lb) | | |

PHYSICAL INTERFACES

| INDEX | DESCRIPTION |
|-------|-------------|
| 1 | VIDEO IN |
| 2 | AUDIO IN |
| 3 | AUDIO OUT |
| 4 | VGA |
| 5 | HDMI |

| INDEX | DESCRIPTION |
|-------|-------------------|
| 6 | USB Interface |
| 7 | Network Interface |
| 8 | Power Supply |
| 9 | Power Switch |
| 10 | GND |

