

## Overview


The Vandal Resistant Reader brings support for a vast amount of functionality encased in a tough IK10 rated construction.

Designed with vandal resistance in mind, the VR Reader includes support for all leading token technology including HID Prox®, MIFARE®, Paxton and EM as well as offering Bluetooth® for communication with long range or handsfree credentials and mobile telephones via the Paxton app.



## Features

- IK10 Rated
- IP67 Rated
- Multi-format reading technology offering compatibility with Paxton, MIFARE, HID Prox®, EM and more
- Built in Bluetooth® Low Energy support to allow communication to mobile and wearable devices
- Simple 4 wire installation
- Brings Paxton simplicity to the plethora of token types currently on the market by supporting all of them concurrently
- Low power sleep mode with capacitive wake-up





## System

Token compatibility	Paxton EM4100/02, Sony®, FeliCa Lite-S MIFARE® Classic, MIFARE®, MIFARE® Plus, DESFire® EV1/EV2, MIFARE Ultralight®, MIFARE Ultralight C®, MIFARE Mini®, NFC®, HID® Prox 125kHz low frequency
---------------------	---



## Electrical

Power consumption	1W (Max)
Operating voltage	12V
Current Draw	40mA (Quiescent) 100mA (Max)



## Communication

RFID Frequency	125kHz & 13.56MHz
Data Connection	RS485/Paxton10 Protocol
Bluetooth®	2.4GHz



## Hardware

Dimensions (W x H x D)	57.6mm x 106mm x 19.5mm
Cable Type	22AWG, 4 core twisted pair
Cable Length	5m / 16ft
Maximum cable extension (Controller – Reader)	100m / 328ft
Sound	Piezo Buzzer
Colour	Black
Housing material	ASTM B86
Warranty	Paxton 5 year



## Environment

Operating temperature	-35°C - +66°C -31°F - +150°F
IP Rating	IP67
IK Rating	IK10
Mounting	Surface only