

LIGHTspeed External Enclosure + Cassette F07 | 48-96F (24xLC Duplex)

The LIGHTspeed outdoor F07 enclosure provides a high-density solution for next generation networks, which aims to provide and manage maximum numbers of fibre terminations in a limited space.

Features

- Indoor & Outdoor use
- Compact design
- Hinged & lockable top cover
- UV & water resistant
- Cable entry access from bottom
- Inlet and outlet ports sealed with rubber grommets
- Integrated fibre splice cassette
- Splicing & patching
- Splice protectors included (24 x 60mm)
- Accommodating PLC metal tube splitter
- Wall Mount kit
 - Pole mount steel brackets included
- Fixing material included



Application

- FTTx access networks – Home / Office
- CATV, LAN & Optical fibre communication

Product Specification

Description	Value
Dimensions (W x H x D)	245mm x 307mm x 81mm
Maximum Splice Capacity	96 Fibres
Adaptor Capacity	24 x SC Simplex 24 x LC Duplex
Splitter Facility	1 x PLC 1x8, 1x16 or 1x32
Cable Entry Port	3 x 14mm Cable OD
Cable Exit Port	24 x 5mm Cable OD
Mounting Options	Pole and Wall
Locking Mechanism	Lock with Key
IP Rating	65

Ordering Information

Product Code	Description
MEGALSPSBFE17	LIGHTspeed External Enclosure + Cassette F07 48-96F (24xLC Duplex)

V 2021/01