

## LIGHTspeed External Enclosure + cassette F06 24F (16xLCD) MEGALSPSBFE16

The LIGHTspeed outdoor F06 enclosure is designed to bring a high speed fibre connection and greater bandwidth closer to home and business. FTTH offers the user flexibility and the opportunity to 'future proof' end to end connectivity with the ever changing technology.

### Features

- Indoor & Outdoor use
- Compact design
- Hinged & lockable top cover
- UV & water resistant.
- Cable entry access from bottom
- Inlet and outlet ports sealed with rubber grommets
- Integrated fibre splice cassette
- Splicing & patching
- Double-deck design.
  - Top - for installing adapters, pigtails, cable management and connecting outer drop cables.
  - Bottom - for splicing fibre and PLC splitter fitting.
- Splice protectors included (16 x 60mm)
- Accommodating PLC metal tube splitter
- Fixing material included



### Application

- FTTx access networks – Home / Office
- CATV, LAN & Optical fibre communication

### Specification

Single fibre count (max)	24	
Splices (max)	24	
Heatshrink splice holders (max)	24 (60mm splice protector)	
Cable entry ports	2 (17 mm)	
Outlet ports	16 (3-5 mm)	
Adaptor holders	16	
Adaptor type	SC Simplex / LC Duplex	
PLC splitter holders	2	
Mounting Application	Wall & Pole (Indoor & Outdoor)	
Dimensions	Height	305 mm
	Width	260 mm
	Depth	95 mm
Material	High Impact Plastic	
Colour	White	
IP Rating	IP 54	