




LigoDLB 5 ac

5GHz High-Capacity Wireless Device

500+ Mbps

Incredible performance

500+ Mbps throughput - a result of powerful hardware platform with 802.11ac technology based radio and a proprietary data transmission protocol (iPoll). Incorporating a QCA 9563 CPU (750MHz), a QCA 9882 radio and 64 MBytes of RAM and 16 MBytes of flash memory, the LigoDLB ac series devices are an ideal solution for capacity demanding applications. State of the art RF design with great output power and sensitivity parameters improve range and capacity over highest the modulation—256-QAM. The 24V Gigabit Ethernet port (passive PoE) allows utilizing the full capacity of the radio when used in a point-to-point or point-to-multipoint network design. LigoDLB ac series devices are backwards compatible with LigoDLB devices using iPoll mode, which helps to expand or upgrade existing networks using the latest technologies over time.



Powerfull OS

The LigoDLB OS is a highly functional and easy to use operating system embedded in all LigoDLB hardware devices for effortless setup and trouble free operation. High performance (500Mbps) allows offering more bandwidth together with additional services such as VoIP and IPTV. This is possible when using LigoWave's smart QoS mechanism and multi-cast traffic enhancements for triple play services. Such services are essential for all next generation service providers to complement their existing portfolios. iPoll, LigoWave's proprietary transmission protocol, ensures smooth performance with a high number of clients even in noisy environments.

Specifications

Distance recommendation	PTMP mode	PTP mode
LigoDLB 5ac	Antenna dependent	Up to 20km (antenna dependent)

Wireless

WLAN standard	IEEE 802.11a/n/ac, iPoll 3
Radio mode	MIMO 2x2
Radio frequency band	5,150 – 5,850GHz (FCC 5,150 – 5,250 and 5,725 – 5,850GHz)
Transmit power	Up to 30dBm (country dependent)
Channel size	5, 10, 20, 40, 80MHz
Modulation schemes	802.11a/n: OFDM (64-QAM, 16-QAM, QPSK, BPSK) 802.11ac: OFDM (256-QAM, 64-QAM, 16-QAM, QPSK, BPSK)
Data rates	802.11ac @ 40MHz: 400, 360, 300, 270, 240, 180, 120, 90, 60, 30Mbps 802.11ac @ 80MHz: 866, 780, 650, 585, 520, 390, 260, 195, 130, 65Mbps
Error correction	FEC, LDPC
Duplexing scheme	Time division duplex

40MHz	Modulation, Mbps	400	360	300	270	240	180	120	90	60	30
	TX Power, dBm	26	27	28	29	30	30	30	30	30	30
	Receive sensitivity, dBm	-70	-72	-76	-78	-80	-84	-87	-92	-94	-95
80MHz	Modulation, Mbps	866	780	650	585	520	390	260	195	130	65
	TX Power, dBm	24	25	25	26	27	28	28	29	29	29
	Receive sensitivity, dBm	-64	-66	-70	-72	-74	-78	-81	-85	-88	-90

Antenna

Type	External N-connectors
Gain	Antenna dependent (up to 20km)

Wired

Interface	10/100/1000 Base-T, RJ45
-----------	--------------------------

Physical

Dimensions	Length 150mm (5.9"), width 115mm (4.5"), height 55mm (2.1")
Weight	450g (1lb)
Mounting	Combination wall / pole mount with quick swap bracket included

Power

Power supply	24VDC passive PoE (AC to 24 VDC adapter is included in the package)
Power source	100 – 240VAC
Power consumption (max)	10W

Environmental

Operating temperature	-40°C (-40°F) ~ +65°C (+149°F)
Humidity	0~90% (non-condensing)

Management

System monitoring	SNMP, Syslog, Web UI, WNMS
Configuration	WebUI, WNMS

Regulatory

Certification	FCC/IC/CE
---------------	-----------



LigoWave

www.ligowave.com

LigoDLB 5ac

Copyright © 2017 LigoWave. All rights reserved. LigoWave, the LigoWave logo, are trademarks of LigoWave. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, LigoWave does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice. To learn more about LigoWave products, visit www.ligowave.com.