

IL-R208W-D

2U Enterprise 8 Bay Video Recording Server







PRODUCT OVERVIEW


The IL-R208W is powered by the High-Performance Intel Xeon Scalable Processor for fast and stable performance.

The Server Features up to 1.5TB of Memory and has up to 176TB of HDD Storage, all in a 2U Rackmount Chassis.

intel.  

KEY FEATURES

-  Up to 176TB of Raw Storage
-  Intel® Xeon® Scalable Processors
-  Redundant OS SSD Drives
-  iDRAC Enterprise
-  Standard Redundant Power
-  Nvidia Workstation GPU Support
-  5 Year NBD Warranty*



Product specifications are provided for informational purposes only, and are subject to change, correction or revision without notice. It is the customer's responsibility to validate product specifications prior to purchase or installation, and to ensure that those specifications are suitable for a particular use. Please refer to the website or reach out to your rep for the latest on products, specs and upcoming product releases at WWW.IRONLINKUSA.COM

IL-R208W-D

2U Enterprise 8 Bay Video Recording Server

SYSTEM

Operating Systems:

Windows Server 2019 /
Windows Server 2022
Windows Server Essentials
Windows Server Embedded
Ubuntu Linux LTS 20.04 / 22.04
Windows 10 IoT Enterprise LTSC /
Windows 11 IoT Enterprise LTSC

Supported CPU:

Up to (2) Intel® Xeon® 2nd
Generation Scalable Processors

Default Memory Configuration:

32GB (4x 8GB)

Up to 1.5TB
(24x DDR4 DIMMs Slots)

Standard Networking:

(6) 1GbE RJ45 Ports &
(2) 10GbE SFP+ ports

Expansion Slots:

(3) PCIe x16 Full-height DW,
(2) PCIe 8x LP

Security Module:

Trusted Platform Module 2.0 v3

MECHANICAL

Form Factor:

2U Rackmount

Power Supplies:

Dual redundant 1100W (100-240VAC)
80 Plus Platinum
*Optional: Dual 1600w (200-240VAC)
80 Plus Platinum*

Bezel:

Lockable Security Bezel

Operating Temperature:

(Min) 50°F - (Max) 95° F
(Min) 10°C - (Max) 35° C

Operating Humidity:

10 to 80% (non-condensing)

Heat Dissipation:

1100w PSU - 4100 Max BTU/hr
1600w PSU - 6000 Max BTU/hr

Dimensions (WxDxH):

17.09" (434mm) x 28.17" (715.5mm) x 3.42"
(86.8mm)

Max. Weight:

73 lbs (33.1 kg)

Warranty:

5-Year, On-site, Next Business Day, Keep Your
Hard Drive Warranty after remote diagnosis
(*onsite drive replacement is dependent on
purchased storage configuration.)

STORAGE

Hard Drive Bays:

(8) 3.5" Hot Swappable Bays &
(2) M.2 SSD Slots

Hard Drives Supported:

SAS, SATA & PCIe NVMe

Supported RAID Levels:

Data drives; 0, 1, 5, 6, & 10
OS m.2 Drives: 0, 1

RAID Controller:

PERC H740 - 8GB NV Cache

Maximum Storage:

Up to 176TB RAW

IO Ports:

Front: 2 x USB 2.0 & 1 x iDRAC
Micro-AB port

Rear: 2 x USB 3.0 ports,
Internal = 1 x USB 3.0 port

Video Outputs:

(1) VGA Port Front &
(1) VGA Port Rear

Remote Management:

iDRAC Enterprise with virtual KVM

Product specifications are provided for informational purposes only, and are subject to change, correction or revision without notice. It is the customer's responsibility to validate product specifications prior to purchase or installation, and to ensure that those specifications are suitable for a particular use. Please refer to the website or reach out to your rep for the latest on products, specs and upcoming product releases at WWW.IRONLINKUSA.COM