



DELL P Series 24 USB-C Hub Monitor - P2422HE

Brand : DELL

Product family: P Series

Product code: DELL-P2422HE

Product name : Dell 24 USB-C Hub Monitor - P2422HE

- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort
- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 1000:1

DELL P Series 24 USB-C Hub Monitor - P2422HE:

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 23.8-inch FHD hub monitor with ComfortView Plus.

DELL P Series 24 USB-C Hub Monitor - P2422HE. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	Headphone out *	✗
Display resolution *	1920 x 1080 pixels	HDCP	✓
HD type *	Full HD	AC (power) in	✓
Native aspect ratio *	16:9	Network	
Display technology *	LCD	Wi-Fi	✗
Panel type *	IPS	Ergonomics	
Backlight type	LED	VESA mounting *	✓
Touchscreen *	✗	Panel mounting interface	100 x 100 mm
Display brightness (typical)	250 cd/m ²	Cable lock slot *	✓
Response time	8 ms	Height adjustment *	✓
Anti-glare screen	✓	Height adjustment	15 cm
Screen shape *	Flat	Pivot	✗
Supported graphics resolutions	1920 x 1080 (HD 1080)	Pivot angle	-90 - 90°
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Swivelling	✓
Aspect ratio	16:9	Swivel angle range	-45 - 45°
Contrast ratio (typical) *	1000:1	Tilt angle range	-5 - 21°
Maximum refresh rate *	60 Hz	On Screen Display (OSD)	✓
Viewing angle, horizontal	178°	Plug and Play	✓
Viewing angle, vertical	178°	LED indicators	Power
Display number of colours *	16.7 million colours	Tilt adjustment	✓
Response time (fast)	5 ms	Power	
Pixel pitch	0.2745 x 0.2745 mm	Energy efficiency class (SDR) *	D
Pixel density	93 ppi	Energy efficiency class (HDR) *	Not available
Horizontal scan range	30 - 83 kHz	Energy consumption (SDR) per 1000 hours *	15 kWh
Vertical scan range	50 - 76 Hz	Power consumption (typical) *	14.5 W
Viewable size, horizontal	52.7 cm	Power consumption (standby) *	0.3 W
Viewable size, vertical	29.6 cm	Power consumption (max)	118 W
Viewable size diagonal	60.5 cm		
Display diagonal (metric)	60.47 cm		

Display		Power	
High Dynamic Range (HDR) supported	✘	Power consumption (off)	0.2 W
Colour depth	6 bit	AC input voltage	100 - 240 V
sRGB coverage (typical)	99%	AC input frequency	50 - 60 Hz
Performance		Power supply type	Internal
Flicker-free technology	✓	Energy efficiency scale	A to G
Low Blue Light technology	✓	Operational conditions	
Multimedia		Operating temperature (T-T)	0 - 40 °C
Built-in speaker(s) *	✘	Storage temperature (T-T)	-20 - 60 °C
Built-in camera *	✘	Operating relative humidity (H-H)	10 - 80%
Design		Storage relative humidity (H-H)	5 - 90%
Market positioning *	Business	Operating altitude	0 - 5000 m
Product colour *	Black	Non-operating altitude	0 - 12192 m
Front bezel colour	Black	Packaging content	
Detachable stand	✓	Stand included	✓
Feet colour	Silver	Cables included	AC, DisplayPort, USB Type-C
Heavy metals free	Hg (mercury)	Quick start guide	✓
Ports & interfaces		Weight & dimensions	
Built-in USB hub *	✓	Width (with stand)	537.8 mm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Depth (with stand)	179.6 mm
USB upstream port type	USB Type-B	Height (with stand)	496.1 mm
Number of upstream ports	1	Weight (with stand)	5.15 kg
Number of USB Type-C upstream ports quantity	1	Width (without stand)	537.8 mm
USB Type-A downstream ports quantity	4	Depth (without stand)	52.1 mm
USB Type-C DisplayPort Alternate Mode	✓	Height (without stand)	318.5 mm
USB Power Delivery up to	65 W	Weight (without stand)	3.39 kg
HDMI *	✓	Bezel width (side)	5.38 mm
HDMI ports quantity	1	Bezel width (top)	5.38 mm
HDMI version	1.4	Bezel width (bottom)	1.67 cm
DisplayPorts quantity	2	Sustainability	
DisplayPort version	1.2	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
		Doesn't contain	PVC/BFR
		Logistics data	
		Harmonized System (HS) code	85285210



5397184505205



5704174872092

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.