DELL

DELL P Series 27 Monitor - P2722H - 68.6cm (27")

Brand : DELL   **Product family:** P Series   **Product code:** DELL-P2722H

Product name : 27 Monitor - P2722H - 68.6cm (27")

- 68.6cm (27") Full HD 1920 x 1080 LED IPS
- 16:9, 300cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort
68.6cm (27") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.7M, 178°/178°, 1000:1

DELL P Series 27 Monitor - P2722H - 68.6cm (27"):

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 27" FHD monitor featuring ComfortView Plus technology.
DELL P Series 27 Monitor - P2722H - 68.6cm (27"). Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 300 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	AC (power) in	✔
Display resolution *	1920 x 1080 pixels	**Network**	
HD type *	Full HD	Wi-Fi	✖
Native aspect ratio *	16:9	**Ergonomics**	
Display technology *	LCD	VESA mounting *	✔
Panel type *	IPS	Panel mounting interface	100 x 100 mm
Backlight type	LED	Cable lock slot *	✔
Touchscreen *	✖	Height adjustment *	✔
Display brightness (typical)	300 cd/m²	Height adjustment	15 cm
Response time	300 ms	Pivot	✔
Anti-glare screen	✔	Pivot angle	-90 - 90°
Screen shape *	Flat	Swivelling	✔
Supported graphics resolutions	1920 x 1080 (HD 1080)	Swivel angle range	-45 - 45°
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Tilt angle range	-5 - 21°
Aspect ratio	16:9	Plug and Play	✔
Contrast ratio (typical) *	1000:1	LED indicators	Power
Maximum refresh rate *	60 Hz	Tilt adjustment	✔
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°	**Power**	
Display number of colours *	16.7 million colours	Energy efficiency class (SDR) *	D
Response time (fast)	5 ms	Energy efficiency class (HDR) *	Not available
Pixel pitch	0.2745 x 0.2745 mm	Energy consumption (SDR) per 1000 hours *	15 kWh
Pixel density	102 ppi	Power consumption (typical) *	15 W
Horizontal scan range	30 - 83 kHz	Power consumption (standby) *	0.2 W
Vertical scan range	50 - 76 Hz	Power consumption (max)	55 W
Viewable size, horizontal	59.8 cm	Power consumption (off)	0.2 W
Viewable size, vertical	33.6 cm	AC input voltage	100 - 240 V
Viewable size diagonal	68.6 cm	AC input frequency	50 - 60 Hz
Display diagonal (metric)	68.6 cm		

Display

High Dynamic Range (HDR) supported	✖
Colour depth	6 bit
sRGB coverage (typical)	99%

Performance

Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Built-in speaker(s) *	✖
Built-in camera *	✖

Design

Market positioning *	Business
Product colour *	Black
Front bezel colour	Black
Detachable stand	✔
Feet colour	Silver
Heavy metals free	Hg (mercury)

Ports & interfaces

Built-in USB hub *	✔
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
Number of upstream ports	1
USB Type-A downstream ports quantity	4
VGA (D-Sub) ports quantity	1
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Headphone out *	✖
HDCP	✔

Power

Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m

Packaging content

Stand included	✔
Cables included	AC, DisplayPort, USB
Quick start guide	✔

Weight & dimensions

Width (with stand)	609.9 mm
Depth (with stand)	190.1 mm
Height (with stand)	384.1 mm
Weight (with stand)	6.77 kg
Width (without stand)	609.9 mm
Depth (without stand)	52.1 mm
Height (without stand)	359.6 mm
Weight (without stand)	4.38 kg
Bezel width (side)	6.01 mm
Bezel width (top)	5.99 mm
Bezel width (bottom)	1.73 cm

Sustainability

Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
Doesn't contain	PVC/BFR

Logistics data

Harmonized System (HS) code	85285210

5397184505236

5704174604327