



DELL P Series 27 USB-C Hub Monitor - P2722HE

Brand : DELL

Product family: P Series

Product code: DELL-P2722HE

Product name : Dell 27 USB-C Hub Monitor - P2722HE

- 68.6cm (27") Full HD 1920 x 1080 LED IPS
- 16:9, 300cd/m², 1000:1
- USB, VGA, HDMI, DisplayPort
- 68.6cm (27") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m², 16.7M, 178°/178°, 1000:1

DELL P Series 27 USB-C Hub Monitor - P2722HE:

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 27-inch FHD hub monitor with ComfortView Plus.

DELL P Series 27 USB-C Hub Monitor - P2722HE. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDCP	✓
Display resolution *	1920 x 1080 pixels	AC (power) in	✓
HD type *	Full HD	Network	
Native aspect ratio *	16:9	Wi-Fi	✗
Display technology *	LCD	Ergonomics	
Panel type *	IPS	VESA mounting *	✓
Backlight type	LED	Panel mounting interface	100 x 100 mm
Touchscreen *	✗	Cable lock slot *	✓
Display brightness (typical)	300 cd/m ²	Height adjustment *	✓
Response time	8 ms	Height adjustment	15 cm
Anti-glare screen	✓	Pivot	✓
Screen shape *	Flat	Pivot angle	-90 - 90°
Supported graphics resolutions	1920 x 1080 (HD 1080)	Swivelling	✓
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Swivel angle range	-45 - 45°
Aspect ratio	16:9	Tilt angle range	-5 - 21°
Contrast ratio (typical) *	1000:1	On Screen Display (OSD)	✓
Maximum refresh rate *	60 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	Power
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.7 million colours	Power	
Response time (fast)	5 ms	Energy efficiency class (SDR) *	D
Pixel pitch	0.3114 x 0.3114 mm	Energy efficiency class (HDR) *	Not available
Pixel density	82 ppi	Energy consumption (SDR) per 1000 hours *	17 kWh
Horizontal scan range	30 - 83 kHz	Power consumption (typical) *	14.5 W
Vertical scan range	50 - 76 Hz	Power consumption (standby) *	0.3 W
Viewable size, horizontal	59.8 cm	Power consumption (max)	118 W
Viewable size, vertical	33.6 cm	Power consumption (off)	0.2 W
Viewable size diagonal	68.6 cm		
Display diagonal (metric)	68.6 cm		

Display		Power	
High Dynamic Range (HDR) supported	✘	AC input voltage	100 - 240 V
Colour depth	8 bit	AC input frequency	50 - 60 Hz
sRGB coverage (typical)	99%	Power supply type	Internal
Performance		Operational conditions	
Flicker-free technology	✓	Operating temperature (T-T)	0 - 40 °C
Low Blue Light technology	✓	Storage temperature (T-T)	-20 - 60 °C
Multimedia		Operating relative humidity (H-H)	
Built-in speaker(s) *	✘	Storage relative humidity (H-H)	10 - 80%
Built-in camera *	✘	Operating altitude	5 - 90%
Design		Non-operating altitude	
Market positioning *	Business	0 - 5000 m	
Product colour *	Black	0 - 12192 m	
Front bezel colour	Black	Packaging content	
Detachable stand	✓	Stand included	✓
Feet colour	Silver	Cables included	AC, DisplayPort, USB
Heavy metals free	Hg (mercury)	Quick start guide	✓
Ports & interfaces		Weight & dimensions	
Built-in USB hub *	✓	Width (with stand)	609.9 mm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Depth (with stand)	190.1 mm
Number of upstream ports	1	Height (with stand)	534.1 mm
Number of USB Type-C upstream ports quantity	1	Weight (with stand)	6.81 kg
USB Type-A downstream ports quantity	4	Width (without stand)	609.9 mm
USB Type-C DisplayPort Alternate Mode	✓	Depth (without stand)	52.1 mm
USB Power Delivery up to	65 W	Height (without stand)	359.6 mm
HDMI *	✓	Weight (without stand)	4.92 kg
HDMI ports quantity	1	Bezel width (side)	6.01 mm
HDMI version	1.4	Bezel width (top)	5.99 mm
DisplayPorts quantity	2	Bezel width (bottom)	1.73 cm
DisplayPort version	1.2	Sustainability	
Headphone out *	✘	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
		Doesn't contain	PVC/BFR
		Logistics data	
		Harmonized System (HS) code	85285210



0884116398110



884116398110



5397184505250



5704174644255



5704174550624

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.