



DELL UltraSharp 27 USB-C Hub Monitor - U2722DE

Brand : DELL

Product family: UltraSharp

Product code: DELL-U2722DE

Product name : Dell UltraSharp
27 USB-C Hub Monitor -
U2722DE

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
- 8ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort
- 68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 1.07B, 8ms, 178°/178°, 1000:1

[DELL UltraSharp 27 USB-C Hub Monitor - U2722DE:](#)

Connected productivity. Vibrant color.

Take your work to new heights with this 27-inch QHD monitor featuring outstanding connectivity, brilliant color coverage including DCI-P3, ComfortView Plus—an always on built-in low blue light screen—and USB-C port with up to 90W power delivery and Ethernet connectivity.

DELL UltraSharp 27 USB-C Hub Monitor - U2722DE. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Silver



Display		Network	
Display diagonal *	68.6 cm (27")	Wi-Fi	✗
Display resolution *	2560 x 1440 pixels	Ergonomics	
HD type *	Quad HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable lock slot *	✓
Panel type *	IPS	Height adjustment *	✓
Backlight type	LED	Height adjustment	15 cm
Touchscreen *	✗	Pivot	✓
Display brightness (typical)	350 cd/m ²	Pivot angle	-90 - 90°
Response time	8 ms	Swivelling	✓
Anti-glare screen	✓	Swivel angle range	-45 - 45°
Screen shape *	Flat	Tilt angle range	-5 - 21°
Supported graphics resolutions	2560 x 1440	On Screen Display (OSD)	✓
Supported video modes	480i, 480p, 576p, 720p, 1080i, 1080p	Plug and Play	✓
Contrast ratio (typical) *	1000:1	Tilt adjustment	✓
Maximum refresh rate *	60 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	E
Viewing angle, vertical	178°	Energy efficiency class (HDR) *	Not available
Display number of colours *	1.07 billion colours	Energy consumption (SDR) per 1000 hours *	20 kWh
Response time (fast)	5 ms	Power consumption (typical) *	20.4 W
Pixel pitch	0.2331 x 0.2331 mm	Power consumption (standby) *	0.3 W
Pixel density	108.78 ppi	Power consumption (max)	197 W
Horizontal scan range	30 - 90 kHz	Power consumption (average)	20.4 W
Vertical scan range	49 - 76 Hz	Power consumption (off)	0.3 W
Viewable size, horizontal	59.7 cm	Power consumption (PowerSave)	20.32 W
Viewable size, vertical	33.6 cm	AC input voltage	100 - 240 V
Viewable size diagonal	68.5 cm	AC input frequency	50 - 60 Hz
High Dynamic Range (HDR) supported	✗		

Display		Power	
RGB colour space	sRGB	Power supply type	Internal
Colour gamut	100%	Energy efficiency scale	A to G
Multimedia		Operational conditions	
Built-in speaker(s) *	✘	Operating temperature (T-T)	0 - 40 °C
Built-in camera *	✘	Storage temperature (T-T)	-20 - 60 °C
Design		Operating relative humidity (H-H)	10 - 80%
Market positioning *	Office	Storage relative humidity (H-H)	5 - 90%
Product colour *	Silver	Operating altitude	0 - 5000 m
Front bezel colour	Black	Non-operating altitude	0 - 12192 m
Detachable stand	✓	Packaging content	
Feet colour	Silver	Cables included	AC, DisplayPort, HDMI, USB Type-C
Heavy metals free	Hg (mercury)	DisplayPort cable length	1.8 m
Ports & interfaces		HDMI cable length	1.8 m
Built-in USB hub *	✓	Weight & dimensions	
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Width (with stand)	611.3 mm
USB upstream port type	USB Type-C	Depth (with stand)	185 mm
Number of upstream ports	2	Height (with stand)	535.1 mm
Number of USB Type-C upstream ports quantity	2	Weight (with stand)	6.59 kg
USB Type-A downstream ports quantity	4	Width (without stand)	611.3 mm
USB Type-C downstream ports quantity	1	Depth (without stand)	49.5 mm
USB Type-C DisplayPort Alternate Mode	✓	Height (without stand)	352 mm
USB Power Delivery up to	90 W	Weight (without stand)	4.78 kg
DVI port	✘	Bezel width (side)	7.3 mm
HDMI *	✓	Bezel width (top)	7.3 mm
HDMI ports quantity	1	Bezel width (bottom)	9.05 mm
HDMI version	1.4	Packaging data	
DisplayPorts quantity	2	Package weight	10 kg
DisplayPort version	1.4	Logistics data	
Audio output	✓	Harmonized System (HS) code	85285210
Headphone connectivity	3.5 mm	Other features	
		Ethernet LAN (RJ-45) ports	1



5397184505014



0884116390787



884116390787



5704174586999



5704174550600

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.