

## DELL P Series 22 Monitor - P2222H

## Brand : DELL

Product family: P Series

Product code: DELL-P2222H

Product name : 22 Monitor -P2222H

- 54.6cm (21.5") Full HD 1920 x 1080 LED IPS - 8ms, 16:9, 250cd/m<sup>2</sup>, 1000:1 - USB, VGA, HDMI, DisplayPort 54.6cm (21.5") Full HD 1920 x 1080 LED IPS, 16:9, 250cd/m<sup>2</sup>, 16.7M, 8ms, 178°/178°, 1000:1

## DELL P Series 22 Monitor - P2222H:

Stay productive no matter where you work. Reduce harmful blue light with this sleek 21.5-inch FHD monitor featuring ComfortView Plus technology.

DELL P Series 22 Monitor - P2222H. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







## Display Network Display diagonal \* 54.6 cm (21.5") Wi-Fi × Display resolution \* 1920 x 1080 pixels Ergonomics Full HD HD type \* VESA mounting \* 1 Native aspect ratio \* 16:9 Panel mounting interface 100 x 100 mm Display technology \* I CD Cable lock slot \* J IPS Panel type \* Height adjustment \* 1 LED Backlight type Height adjustment 15 cm Touchscreen \* × Pivot 1 250 cd/m<sup>2</sup> Display brightness (typical) -90 - 90° Pivot angle 8 ms Response time Swivelling 1 Anti-glare screen 1 Swivel angle range -45 - 45° Screen shape \* Flat Tilt angle range -5 - 21° 1920 x 1080 (HD 1080) Supported graphics resolutions On Screen Display (OSD) 1 Supported video modes 480p, 576p, 720p, 1080i, 1080p Plug and Play 1 Aspect ratio 16:9 LED indicators Power 1000:1 Contrast ratio (typical) \* Tilt adjustment 1 60 Hz Maximum refresh rate \* Power Viewing angle, horizontal 178° 178° Energy efficiency class (SDR) \* D Viewing angle, vertical Display number of colours \* 16.7 million colours Energy efficiency class (HDR) \* Not available Energy consumption (SDR) per 1000 Response time (fast) 5 ms 12 kWh hours Pixel pitch 0.248 x 0.248 mm 11.8 W Power consumption (typical) \* Pixel density 102 ppi Power consumption (standby) \* 0.3 W Horizontal scan range 30 - 83 kHz 46 W Power consumption (max) 56 - 76 Hz Vertical scan range Power consumption (off) 0.2 W Viewable size, horizontal 47.6 cm 100 - 240 V AC input voltage Viewable size, vertical 26.8 cm 50 - 60 Hz AC input frequency Viewable size diagonal 54.6 cm Power supply type Internal Display diagonal (metric) 54.61 cm

Display		Power	
High Dynamic Range (HDR)	×	Energy efficiency scale	A to G
supported sRGB coverage (typical)	99%	Operational conditions	
Performance	5570	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Flicker-free technology Low Blue Light technology	1 1	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 80% 5 - 90%
Multimedia		Operating altitude	0 - 5000 m
Built-in speaker(s) *	×	Non-operating altitude	0 - 12192 m
Built-in camera *	×	Packaging content	
Design		Stand included	4
Market positioning *	Business	Cables included	AC, DisplayPort, USB
Product colour *	Black	Quick start guide	1
Front bezel colour	Black	Weight & dimensions	
Detachable stand	4	Width (with stand)	487.3 mm
Feet colour	Silver	Depth (with stand)	179.6 mm
Heavy metals free	Hg (mercury)	Height (with stand)	482 mm
Ports & interfaces		Weight (with stand)	4.57 kg
Built-in USB hub *	✓	Width (without stand)	487.3 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Depth (without stand)	52.1 mm
USB upstream port type	USB Type-B	Height (without stand)	290 mm
Number of upstream ports	1	Weight (without stand)	2.82 kg
USB Type-A downstream ports	4	Bezel width (side)	5.6 mm
quantity	-	Bezel width (top)	5.6 mm
VGA (D-Sub) ports quantity	1	Bezel width (bottom)	1.66 cm
HDMI *	4	Packaging data	
HDMI ports quantity	1	Package weight	6.37 kg
HDMI version	1.4		5
DisplayPorts quantity	1	Sustainability	
DisplayPort version	1.2	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
Headphone out *	×	Doesn't contain	PVC/BFR
HDCP	4	Logistics data	
AC (power) in	1	Harmonized System (HS) code	85285210



5397184505144



5704174809159

5704174787563

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.