

# 4+2-Port 10/100 Mbps PoE Switch

PoES-0460C+2I



- Downlink: 4x100Mbps Ports
- Uplink: 2x100Mbps Port
- 60W(Avg:15W Max 30W per ch)
- Distance: Up to 100 Meter
- Built-in Surge Protection
- Built-in Power Supply
- Complies With IEEE802.3af/at
- CCTV mode:
  - Up to 250 meter at 10Mbps
  - Vlan function: no communication among downlink ports
  - Wall Bracket/Anti-Theft Hole Lock(k-slot)/Earthing Connector

## Specifications

MODEL	PoES-0460C+2I	
Interface	Downlink Ports	4 x 10/100Mbps
	Uplink Ports	2 x 10/100Mbps
	SFP Ports	No
PoE	PoE Ports	4 (Downlink Ports)
	PoE Standard	IEEE802.3af/at PoE
	PoE Total Power	60W
	Average Power Per Channel	15W
	Maximum Power Per Channel	30W
Data Processing	Backbone Bandwidth	1.2Gbps
	Buffer Size	448Kb
	MAC Address Table	1K
	VLAN	Auto (In CCTV Mode)
Network Media	EIA/TIA-568	100Ω STP (Maximum 100m)
	10BASE-T	UTP Category 3, 4, 5 Cable (Maximum 100m)
	100BASE-TX	UTP Category 5, 5e Cable (maximum 100m)
	1000BASE-T	Not Supported
Special	CCTV Mode	Selectable Standard/CCTV Mode
	Surge Protector	Built-In
	Wall Bracket	Available (Wall installation)
	Rack Bracket	No
	K-Slot (Anti Theft)	No
Power	PoE Status Monitor	No
	Power Supply	100-240VAC
Others	Power Consumption	PoE On: 63W Max. / PoE Off: 3W Max.
	Fan	No
	Dimensions	168*94*32 mm
	Weight	850gr
	Operating Temperature	-10°C~50°C



CCTV Mode Switch



100-240AC Power Input