

IP SPECIAL SERIES

Provision-ISR's special IP cameras come to the aid of the security professional who is facing the most uncommon requests. The series includes discrete, c-mount, fisheye, Wireless and PIR cameras.



I3-330WIP536-M

30M IR 3MP FIXED LENS BULLET CAMERA

The I3-330WIP536-M is the best solution when wired network is not available. When paired with the WP-04IPC, the I3-330WIP536-M will transform to a wireless camera that can be easily paired with any NVR via ONVIF. It is equipped with high resolution 3MP sensor and wide 3.6mm fixed lens



I3-330WIP536-M Must be paired with WR-04IPC-V2 adapting unit in order to work with Provision-ISR NVR

MAIN FEATURES

- 3MP
- Wireless IP
- 2304x1296 Resolution
- Wide field of view 90°
- 3D-DNR
- IP66



SPECIFICATIONS

Image Sensor	1/3" CMOS (16:9)
Effective Pixels	2304x1296
Electronic Shutter	1/25s ~ 1/100000s
Frame Rate	1-15FPS
Day & Night	ICR
Min. Illumination	0.1 lux (@F2.0, AGC ON) 0 lux with IR on
Audio compression	No
Communication	-
Image Settings	Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement	Digital WDR
Noise Reduction	3D-DNR
Image Orientation	-
Privacy Zone	-
Motion Detection	Yes
Analytics	-
Video Compression	H.265 / H.264
Resolution	3MP / 2MP / 640x360
Multi-Stream	Master Stream: 3MP(2304x1296) / 2MP(1920x1080) Sub-Stream: 640x360
Bit rate	32Kbps ~ 10Mbps
Encode Mode	VBR/CBR
Image Quality	Five levels under VBR; Free adjustment under CBR
IR Distance	30m (3 High Power IR LED)
Lens (Field of View)	3.6mm (90°)

SPECIFICATIONS

Iris	Fixed Iris
Lens Mount	M12 mount
Protection Rate	Water Proof: IP66
Bracket	3-Axis Bracket
Dimensions	Water Proof: IP66
Weight (gross)	-
Network	Wireless Only (With WR-04IPC Adapter)
Power	DC Socket
Analog Video Output	No
Audio Connectivity	No
SD Card	No
Hard Reset Button	Yes
Alarm	No
Remote Monitoring	Ossia VMS Software
User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS
ONVIF	Yes
Ethernet	100Mbps
PoE	No
Power Supply	DC12V/~520mA
Work Environment	-20°C~50°C, 10%~90% Humidity
Junction Box	-