

## NVR SERIES


Provision-ISR conventional NVRs are for obtaining video streams from the IP cameras via the IP networks for their storage and subsequent playback. These devices communicate with the IP cameras through the general network, without the need for a direct IP camera connection, providing the installer with the highest flexibility when designing the system and the wiring.



# NVR8-32800FA(1U)

## 32CH 8MP FACE RECOGNITION NVR WITH ALARMS

Provision-ISR NVR8-32800FA(1U) is a high-performance network video recorder supporting Face Recognition and Advanced Video Analytics (DDA). The device, suitable for big-sized installations (up to 32 channels), features 8 alarm inputs + 4 alarm outputs and provides everything you need for a trouble-free CCTV project.



### MAIN FEATURES

- Channels: 32 over Network
- Video output: HDMI (4K,1080P) VGA (1280X1024)
- Max. Recording: 32CH 8MP Real-Time
- HDD: 2 SATA (10TB each) with Smart Management
- Alarms: 8 In / 4 Out (+ IPC Inputs/Outputs)
- Audio: 1 In / 1 Out (+ IPC Inputs/Outputs)
- Video Analytics: Yes (Must be supported by IPC)
- DDA, Face recognition, LPR and Fish-Eye support



# NVR8-32800FA(1U)



## SPECIFICATIONS

	Input	32Ch over Network
	Output	HDMI1 (4K 30/60Hz, 1080P, 1280x1024, 1024x768), HDMI2 + VGA (1080P, 1280x1024, 1024x768)
Video	View Mode	Independent, Up to 32ch on monitor1 + 4ch on monitor2 *Under Advanced Face Recognition Mode: Up to 24ch on monitor1
	Decoding Format	H.265 / H.265+ / H.265S / H.264
	Decoding Capabilities	1Ch - 8MP ; 4Ch - 2x8MP + 2x5MP ; 9/16Ch - 1MP ; 32Ch - D1
	Input	1CH RCA (Linear, 1kΩ) + IPC Inputs
Audio	Output	1CH RCA (2.0 Vp-p, 1 kΩ) + IPC Inputs
	Compression	G.711A/G.711U
	Two Way Audio	Yes
	Analytics Channels	32Ch (Requires supporting IPC) Advanced Face Recognition Mode: Up to 2 Non-AI IPC
Analytics	Supported Analytics	Camera Tampering, Line Crossing (DDA / Pixel Based), Sterile Area (DDA / Pixel Based), Object Monitoring, Object Counting (DDA), Crowd Gathering, People Intrusion, Smart Search, Face Recognition, LPR. Advanced Face Recognition Mode: Supports up to 2 Non-AI IPC and performs face detection and recognition.
	Face Recognition Rate	180 Faces per minute (All Channels) / 3 Faces per second (Single Channel)
Bandwidth	Incoming	192Mbps
	Outgoing	192Mbps
	Real-Time Recording	32CH 8MP Real-Time
Record / Remote App Record/ Main Stream	Record Type	Video / Video + Audio
	8MP	960FPS (NTSC)/800FPS (PAL)
	5MP and lower	960FPS (NTSC)/800FPS (PAL)
	Master stream over network	Up to 32CH@Recording Resolution

## SPECIFICATIONS

Sub Stream	Resolution	Depends on IPC
	Substreams over Network	Up to Outgoing Bandwidth Capacity
General	Recording Modes	Schedule, Manual, Motion, Sensor, Analytics, POS and all combinations
	User Access	20 Users online with Professional Authority Management
Record / Remote App	Mobile App	Provision Cam2 for iOS/Android
	PC/Mac Software	Ossia VMS Standard / Enterprise
	Plug-in free Web-Browser	Chrome, FireFox, Safari, Edge, Opera. (All Limited to 4Ch Live View / Playback)
	Plug-in based Web-Browser	Internet Explorer
Playback	Local Playback	16Ch
	Remote Playback (Web, App, VMS)	32Ch
Backup	Search Mode	DDA Object, Smart Search, LPR, Face Recognition, Time-Slice, Time, Event, POS
	USB	2 USB 2.0 Port + 1 USB 3.0 Port
	Backup Format	AVI (Unencrypted) / Private Format (Encrypted / Unencrypted)
Alarm	Input	8+IPC
	Output	4+IPC
Storage	HDD	2
	E-SATA	None
	Max Capacity	20TB (Up to 10TB Each)
	RAID	N/A

## SPECIFICATIONS

	Connection	Via Network
PTZ	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	Yes (C06 Keyboard Connection)
Network	Ethernet	2x1000/100/10Mbps self-adaptive Ethernet interface with Fault Tolerance / Dual Network Configuration
	Protocols	TCP/IPv4/IPv6, DHCP, DDNS, NTP, SMTP, SSL/TLS, UPnP, P2P, RTSP, FTP, HTTPS, 820.1X, SNMP, Auto Report (Ossia VMS)
	ONVIF	Full Device Support (Profile T/G, ONVIF Version 20.12)
	Ports	N/A
	Speed	N/A
PoE	Standard	N/A
	CCTV Mode	N/A
	Total Power	N/A
	Max. Power Output (Per Ch.)	N/A
	Power Supply	DC12V/4A
Others	Power consumption (No HDD)	15W
	Dimension	W375xD275xH50mm
	Operation Temperature	0C° - 50C°

\*Max power output will be reduced depending on cable quality and distance.