



Fence light - Timed

The fence light flashing rate changes with the change of voltage on the fence. The slower the rate the lower the voltage. The intensity of the light remains the same so it can be seen from far irrespective of the fence voltage. It is installed between the earth and live wire to indicate the status and condition of the fence for peace of mind.

Features

Indicates power on the fence for peace of mind

- Visible from up to 1km at night and 100m during the day
- No batteries required
- Uses minimal power from the fence
- The frequency of the flashing LEDs indicates the amount of energy on the fence. The longer the period between flashes, the lower the voltage on the fence
- Highly visible LEDs allow for a 160-degree viewing angle. This allows the light to shine into the secure area only
- Can operate from 0.9kV to 12kV
- Can be used with most electric fence energizers

Specifications:

Material: Plastic and water tight compound

Steel wire connectors: Galvanised (Brown housing) or stainless steel (Blue housing) option

Waterproof Housing IP66

Flashing rates:

- 1. Flashing normally rate over ~7.5kV
- 2. Flashing at 25% slower than normal between 7.5kV~3kV
- 3. Flashing at 50% slower than normal between 3kV~2.5kV
- 4. Flashing at 75% slower than normal when less than ~2.5kV

https://www.nemtek.co.za/HomeSecurity/General-Accessories/fence-light-timed.aspx.

Stock Code	Name	Description
SR-FL/TL/G	Fence light - Timed	Fence Light HV - Timed- Galv Dark Grey
SR-FL/TL/SS	Fence light - Timed	Fence Light HV - Timed - S/Steel Blue