

THC-B127-LPC 2 MP Dual-Light Fixed Mini Bullet Camera



- High quality imaging with 2 MP, 1920 × 1080 resolution
- Smart-Hybrid light, optimize your security with flexible lighting options
- 2.8 mm, 3.6 mm fixed focal lens
- Up to 20 m IR distance for bright night imaging
- Up to 20 m white light distance for bright night imaging
- One port for 4 switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP66)

▪ Specification

| Camera | |
|--------------------------|---|
| Image Sensor | 2 MP CMOS |
| Max. Resolution | 1920 (H) × 1080 (V) |
| Min. Illumination | 0.02 Lux @ (F2.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0 to 360°, Tilt: 0 to 75°, Rotate: 0 to 360° |
| Signal System | PAL/NTSC |
| Lens | |
| Lens Type | 2.8 mm, 3.6 mm fixed focal lens |
| Focal Length & FOV | 2.8 mm, horizontal FOV: 97°, vertical FOV: 54°, diagonal FOV: 113° 3.6 mm, horizontal FOV: 77°, vertical FOV: 43°, diagonal FOV: 90° |
| Lens Mount | M12 |
| Illuminator | |
| Supplement Light Type | White Light,IR |
| Supplement Light Range | IR : Up to 20 m White Light : Up to 20 m |
| Image | |
| Image Parameters Switch | STD/HIGH-SAT/HIGHLIGHT |
| Image Settings | Brightness, Sharpness, Smart IR |
| Frame Rate | TVI: 1080p @ 30 fps, 1080p @ 25 fps AHD: 1080p @ 30 fps, 1080p @ 25 fps CVI: 1080p @ 30 fps, 1080p @ 25 fps CVBS: PAL/NTSC |
| Wide Dynamic Range (WDR) | Digital WDR |
| Image Enhancement | DWDR/BLC/HLC/Global |
| White Balance | Auto/Manual |
| AGC | Yes |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| General | |
| Material | Plastic |
| Dimension | ∅70 mm × 153.4 mm (∅2.76" × 6.04") |
| Weight | Max. 145 g (0.32 lb.) |
| Operating Condition | -40 °C to 60 °C (-40 °F to 140 °F). Humidity: 90% or less (non-condensation) |
| Communication | HIKVISION-C |
| Language | English |
| Power Supply | 12 VDC ± 25%, Max. 3.2 W *You are recommended to use one power adapter to supply the power for one camera. |
| Approval | |
| Protection | IP66 |


▪ Available Model

THC-B127-LPC(2.8mm)

THC-B127-LPC(3.6mm)

THC-B127-LPC(3.6mm)(IRQ DIGITAL)




▪ Dimension



Unit: mm (inch)

▪ Accessory

▪ Optional

| DS-1280ZJ-XS Junction box | DS-2280ZJ Wall mount |
|---|--|
|  |  |
|  | |

HiLook

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

