

DH-HAC-HMW3200L-FR

2MP Double-lens HDCVI Mobile IR Camera



- Max 30fps@1080p
- CVI/CVBS/AHD/TVI switchable
- Built-in Mic
- 2.1 mm fixed lens
- Max. IR length 3 m, Smart IR
- DC12V
- Shock-proof



System Overview

Experience a 1080p full HD mobile video surveillance solution with the simplicity of analog infrastructure. The mobile camera is designed with a shock-proof, compact case, which makes it convenient to install and adaptable to various applications. It offers a high quality image as well as a multi-language OSD. In addition, the camera employs the strengths of HDCVI to ensure real-time transmission.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Shock-proof

Vibration is inevitable in mobile applications. In order to avoid image or connection failure, the hardware structure of the mobile camera is shock-proof with the certification of EN50155. Plus, the mobile camera adopts M12 aviation connector for stable connection with MCVR.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself the best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Technical Specification					
Camera					
Image Sensor		1/2.7 inch CMOS			
Max. Resolution		1920 (H) x 1080 (V)			
Pixel		2MP			
Scanning System		Progressive			
Electronic Shutter Speed		PAL: 1/25 s–1/100000 s NTSC: 1/30 s–1/100000 s			
S/N Ratio		>65 dB			
Min. Illumination		0.02 Lux/F2.0, 30IRE, 0 Lux IR on			
Illumination Distance		3 m (9.8 ft)			
Illuminator On/Off Control		Auto; manual			
Illuminator Number		1 (IR)			
Pan/Tilt/Rotation Range		Pan: 30° Tilt: 30° Rotation: 360°			
Lens					
Lens Type		Fixed-focal			
Mount Type		M12			
Focal Length		Front: 2.8 mm Rear: 2.1 mm			
Max. Aperture		F2.0			
Field of View		Front: H: 109°; V: 58°; D: 127° Rear: H: 132°; V: 69°; D: 164°			
Iris Type		Fixed iris			
Close Focus Distance		0.5 m (1.64 ft)			
DORI Distance		Detect	Observe	Recognize	Identify
	Front	42.8 m (140.4 ft)	17.7 m (58.1 ft)	8.6 m (28.2 ft)	4.3 m (14.1 ft)
	Rear	35.5 m (116.5 ft)	14.2 m (46.6 ft)	7.1 m (23.3 ft)	3.5 m (11.5 ft)
Video					
Frame Rate		CVI: 1080p@25/30fps; 720p@25/30fps; 720p@50/60fps; AHD: 1080p@25/30fps; 720p@25/30fps; TVI: 1080p@25/30fps; 720p@25/30fps; 720p@50/60fps; CVBS: 960H			
Resolution		1080p (1920 × 1080); 720p (1280 × 720); 960H (960 × 576/960 × 480)			
Day/Night		Front: Color Rear: Electronic			
BLC		BLC/HLC/DWDR			
WDR		DWDR			
White Balance		Auto; manual			
Gain Control		Auto; manual			

Noise Reduction		2D NR
Smart IR		Yes
Mirror		Off/On
Privacy Masking		Off/On (8 area, rectangle)
Certifications		
Certifications	CE/FCC	
Port		
Audio Interface	Built-in Mic	
Video Output	2-channels CVI/CVBS/AHD/TVI switchable video output (Aviation connector) (Yellow: front camera/black: rear camera)	
Aviation Connector Interface	1-power 2-video ground 3-power ground 4-video	
Power		
Power Supply	12V ±30% DC	
Power Consumption	Max 1.9W (12V DC, IR on)	
Environment		
Operating Temperature	−40°C to +60°C (−40°F to 140°F); <95% (non-condensation)	
Storage Temperature	−40°C to +60°C (−40°F to 140°F); <95% (non-condensation)	
Structure		
Casing	Plastic	
Dimensions	115.8 mm × 99.5 mm × 50.2 mm (4.56" × 3.92" × 1.98")	
Net Weight	0.17 kg (0.37 lb)	
Gross Weight	0.28 kg (0.37 lb)	

Ordering Information		
Type	Part Number	Description
2MP Camera	DH-HAC-HMW3200LP-FR 2.1 mm	2MP Double-lens HDCVI Mobile IR Camera, PAL
	DH-HAC-HMW3200LN-FR 2.1 mm	2MP Double-lens HDCVI Mobile IR Camera, NTSC

Aviation Connector

Dimensions (mm[inch])

