

KR Series

Card Readers



KR100-E/M



KR101-E/M




KR102-E/M



KR503-E/M



KR500-E/M



KR501-E/M



KR502-E/M

RFID/Mifare Card Readers

Part Numbers

KRxxx-E: 125 KHz Proximity Card Reader

KRxxx-M: 13.56 MHz Mifare Card Reader

Reading Time

<300ms

Input Port

External LED Control
External Buzzer Control

Output Format

E-Models
26bit Wiegand
1's/5's M-Models
Default: 26 bit format
(Optional 34 bit format available)

Power/Current

6-14V DC/70mA

LED

Red and Green LEDs

Beeper

Yes

Operating Temperature

14F° to 158F° (-10° to +70°C)

Operating Humidity

10% to 90% relative humidity non-condensing

Index of Protection

Waterproof IP65
Reverse Polarity Protection

Dimensions

	KR100 E/M	KR101 E/M	KR102 E/M	KR500 E/M	KR501 E/M	KR502 E/M	KR503 E/M
Height:	4.57in (11.6cm)	3.05in (7.75cm)	3.39in (8.6cm)	4.57in (11.6cm)	3.39in (8.6cm)	3.39in (8.6cm)	4.57in (11.6cm)
Length:	2.95in (7.5cm)	1.69in (4.28cm)	3.39in (8.6cm)	2.95in (7.5cm)	3.39in (8.6cm)	3.39in (8.6cm)	2.95in (7.5cm)
Width:	0.69in (1.75cm)	0.65in (1.65cm)	0.65in (1.63cm)	0.68in (1.73cm)	0.63in (1.6cm)	0.79in (2.0cm)	0.68in (1.73cm)
Weight:	0.35lbs (0.16kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.15lbs (0.07kg)	0.30lbs (0.14kg)	0.30lbs (0.14kg)	0.35lbs (0.16kg)



Design and Specifications subject to change without notice

ZKAccess

201 Circle Drive North, Suite 116
Piscataway, NJ 08854, USA
Tel: +1 732-412-6007
Fax +1 732-412-6008

sales@zkaccess.com
zkaccess.com

