



802.11ax Tri-Band Wi-Fi 6E Access Point

GWN7665

The GWN7665 is a powerful, enterprise-grade Wi-Fi 6E access point, ideal for small-to-medium sized businesses, multiple floor buildings, residential settings and commercial locations. It offers tri-band 2x2:2 MU-MIMO with DL/UL OFDMA technology and a sophisticated internal antenna design for stronger anti-interference, more stable connection, maximum network throughput and expanded Wi-Fi coverage range. The GWN7665 is supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform that makes managing your network or several networks across multiple locations easier than ever before. It also uses a controller-less network management architecture in which the controller is embedded within the product's web user interface for easy administration of locally deployed Wi-Fi APs. The GWN7665 is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals, 384 concurrent clients and dual Gigabit network ports with PoE/PoE+, the GWN7665 is an ideal Wi-Fi access point for business-grade wireless network deployments with medium-to-high user density.



5.4Gbps aggregate wireless throughput 3.5 Gigabit wireline ports



Tri-band 2x2:2 MU- MIMO with DL/UL OFDMA technology



Up to 175-meter coverage range



Support 384 concurrent Wi-Fi client



Advanced QoS to ensure real-time performance of low-latency applications



Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device



Self power adaptation upon auto detection of PoE or PoE+



Embedded controller manages up to 50 local GWN APs; GWN.Cloud offers unlimited AP management, & GWN Manager offers on-premise software AP management

| | |
|--|--|
| Wi-Fi Standards | IEEE 802.11 a/b/g/n/ac/ax |
| Antennas | 7 individual internal antennas 2.4GHz x 2, gain 4.0dBi 5 GHz x 2, gain 5.0dBi 6 GHz x 2, gain 4.5dBi BT, gain 4.0dBi |
| Wi-Fi Data Rates | 2.4G: IEEE 802.11ax: 7.3 Mbps to 573.5 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 5G: IEEE 802.11ax: 7.3 Mbps to 2403 Mbps IEEE 802.11ac: 6.5 Mbps to 1734 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 6G: IEEE 802.11ax: 7.3 Mbps to 2403 Mbps IEEE 802.11ac: 6.5 Mbps to 1734 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps <i>*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network</i> |
| Frequency Bands | 2.4GHz Radio: 2412 - 2484 MHz 5GHz Radio: 5180 - 5825 MHz 6GHz Radio: 5945 -7125MHz <i>*Not all frequency bands can be used in all regions</i> |
| Channel Bandwidth | 2.4G: 20 and 40 MHz 5G: 20, 40 80 and 160 MHz 6G: 20, 40 80 and 160MHz |
| Wi-Fi and System Security | WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/ control lockdown via digital signatures, unique security certificate and random default password per device |
| MU-MIMO | 2x2:2 2.4GHz 2x2:2 5GHz 2x2:2 6GHz |
| Coverage Range | Up to 175 meters <i>*coverage range can vary based on environment</i> |
| Maximum TX Power | 2.4G: 24dBm 5G: 27dBm 6G: 26 dBm <i>*Maximum power varies by country, frequency band and MCS rate</i> |
| Receiver Sensitivity | 2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11 5G 802.11a: -90dBm @6Mbps, -72dBm @54Mbps; 802.11n 20MHz: -71dBm @MCS7; 802.11n 40MHz:-68dBm @MCS7; 802.11ac 20MHz: -65dBm@MCS8; 802.11ac: 40MHz:- 61dBm @MCS9; 802.11ac 80MHz: -57dBm @MCS9;802.11ac 160MHz: -55dBm @MCS9; 802.11ax 20MHz: -58dBm @MCS11; 802.11ax 40MHz: -56dBm @MCS11;802.11ax 80MHz: -54dBm @MCS11;802.11ax 160MHz: -51dBm @MCS11 6G 802.11a: -90dBm @6Mbps, -72dBm @54Mbps; 802.11n 20MHz: -71dBm @MCS7; 802.11n 40MHz:-68dBm @MCS7; 802.11ac 20MHz: -65dBm@MCS8; 802.11ac: 40MHz:- 61dBm @MCS9; 802.11ac 80MHz: -57dBm @MCS9;802.11ac 160MHz: -55dBm @MCS9; 802.11ax 20MHz: -58dBm @MCS11; 802.11ax 40MHz: -56dBm @MCS11;802.11ax 80MHz: -54dBm @MCS11;802.11ax 160MHz: -51dBm @MCS11 |
| SSIDs | 48 SSIDs total, 16 per radio (2.4GHz & 5GHz & 6GHz) |
| Concurrent Clients | 384 |
| Network Interfaces | 1x autosensing 10/100/1000 Base-T Ethernet Port 1x autosensing 10/100/2500 Base-T Ethernet Port |
| Auxiliary Ports | 1x Reset Pinhole, 1x Kensington lock |
| Mounting | Indoor wall mount or ceiling mount, kits included |
| LEDs | 3 tri-color LEDs for device tracking and status indication |
| Network Protocols | IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM |
| QoS | 802.11e/WMM, VLAN, TOS |
| Network Management | Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs |
| Power and Green Energy Efficiency | PoE 802.3at Maximum Power Consumption: 22.55W |
| Environmental | Operation: 0°Cto 50°C Storage: -10°C to 60°C Humidity: 10% to 95% Non-condensing |
| Physical | Unit Dimension: 205.3mmx205.3mmx45.9mm; Unit Weight: 765g Entire Package Dimension: 258mmx247mmx86mm; Entire Package Weight: 1106g |
| Package Content | GWN7665 Wireless AP, Mounting Kits, Quick Start Guide |
| Compliance | FCC, CE, RCM, IC,UKCA |