

8MP 16CH NVR with alarms, check point protection, and NDAA compliance

Provision-ISR's NVR8-16400AN(1U) is an easy-to-install solution for mid-sized installations (up to 16 channels). Check Point Quantum IoT Nano agent is integrated into this model. It provides an advanced threat prevention layer against the common attack vectors at runtime. The device complies with NDAA demands. It features 4 alarm inputs + 1 alarm output and provides you with everything you need for a trouble-free CCTV project.































MAIN FEATURES

Video:

- Input: 16 Channel Support
- 16 Channel Standard Connection (Via RJ-45 Network Port)
- Output: HDMI (4K, 1080P), VGA (1080P, 1280×1024, 1024×768)

Bandwidth:

- Incoming: 96Mbps
- Outgoing: 96Mbps

Decoding Support:

H.265S/H.265+/H.265/H264

Analytics

- Camera Tampering, DDA2 With Object Classification, Line Crossing (DDA / Pixel Based), Sterile Area (DDA / Pixel Based), Object Monitoring, Object Counting (DDA), Crowd Gathering, People Intrusion, Smart Search, LPR, Thermal
- *DDA/LPR Analytics Live Snapshots are not supported

Recording:

- 16CH 8MP Real-Time
- FPS: 400 (PAL) / 480 (NTSC)

Playback:

- Local: 16Ch Simultaneously
- Remote: 16Ch Simultaneously

Audio:

- Input: 1CH + IPC Inputs
- Output: 1CH + IPC Output
- 2 Way Audio

Alarm:

- Input: 4+IPC
- Output: 1+IPC

Storage

• 2 x SATA (Up to 10TB each)

USB Port:

• 2 USB 2.0 Port

Network:

• 1 x RJ-45: 10/100/1000Mbps Each

Remarks:

• The following features are based on firmware v1.4.7 and are subject to firmware version changes.





SPECIFICATIONS

3rd Party Cyber Protection	
General Quantum IoT Nano agent by Ch	eck Point™
Protection Methods Shell injection protection, File M Memory Protection	lonitor, Import-Table Protection, Dynamic-
NDAA Compliant	
NDAA Compliant Yes	
Video	
Video Input 16Ch over Network	
Output HDMI (4K, 1080P), VGA (1080P,	1280x1024, 1024x768)
View Mode Mirrored	
Fish-Eye Dewarp Web Only	
Decoding Format H.265 / H.265+ / H.265S / H.264	
Decoding Capabilities 1Ch – 8MP ; 4Ch – 2MP ; 9/16Ch	- D1
Audio	
Audio-specs-Input 1CH RCA (Linear, 1kΩ) + IPC inp	uts
audio-specs-Output 1CH RCA (2.0 Vp-p, 1 k Ω) + IPC of	outputs
Compression G.711A/G.711U	
Two Way Audio Yes	
Analytics	
Based), Sterile Area (DDA / Pixe	Object Classification, Line Crossing (DDA / Pixel Based), Object Monitoring, Object Counting Intrusion, Smart Search, LPR, Thermal nots are not supported
Analytics Channels (IPC Based) 16Ch (Requires supporting IPC)	
Analytic Channels (NVR Based)	
Face Recognition Rate N/A	
Bandwidth	



Outgoing	96Mbps		
Record/ Main Stream	Record/ Main Stream		
Real-Time Recording	16CH 8MP Real-Time		
Record Type	Video / Video + Audio		
Recording Modes	Schedule, Manual, Motion, Sensor, Analytics, POS and all of the combinations		
16MP	N/A		
12MP	N/A		
8MP	480FPS(NTSC)/400FPS(PAL)		
5MP and lower	480FPS(NTSC)/400FPS(PAL)		
Master stream over network	Up to 16CH@Recording Resolution		
Substream			
Resolution substream	Depends on IPC		
Remote view			
Max Channel View	80Ch (Limited to Outgoing Bandwidth Capacity)		
Remote Applications			
User Access	10 Users Online with Professional Autorithy Management		
Mobile App	Provision Cam2 for iOS/Android		
PC/Mac Software	Ossia VMS Standard / Enterprise		
Plug-in free Web-Browser	Chrome, FireFox, Safari, Edge, Opera. (All Limited to 4Ch Live View / Playback) *P2P WEB connetion always requires Plugin		
Plug-in based Web-Browser	Internet Exporer		
Playback			
Local	16Ch		
Remote	16Ch		



Search Mode	DDA Object, Smart Search, LPR, Time-Slice, Time, Event, POS	
Backup		
USB	2 USB 2.0 Port	
Backup Format	AVI (Unencrypted) / Private Format (Encrypted / Unencrypted)	
Alarm		
Alarm-in	4+IPC	
Alarm-out	1+IPC	
Storage		
HDD	2	
E-Sata Support	No	
RAID	N/A	
PTZ		
Connection	Via Network	
Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus	
RS-485	N/A	
Network		
Ethernet	1000/100/10Mbps self-adaptive Ethernet interface	
Protocols	TCP/IPv4/IPv6, DHCP, DDNS, NTP, SMTP, SSL/TLS, UPnP, P2P, RTSP, FTP, HTTPS, 820.1X, SNMP, Auto Report (Ossia VMS)	
ONVIF	Full Device Support (Profile T/G, ONVIF Version 20.12)	
PoE		
PoE Ports	N/A	
Speed	N/A	
Standard	N/A	



CCTV Mode	N/A
Total Power	N/A
Max. Power Output (Per Ch.)	N/A

Others	
Power Supply	DC12V/4A
Power consumption (No HDD)	5W
Dimension	W375xD275xH50mm
Operation Temperature	0°C~50°C



DIMENSIONS

