



AC1200 Wireless Dual Band Gigabit Router

Archer C5

- Superfast dual band Wi-Fi, up to 1.2Gbps Wi-Fi speed, 300Mbps 2.4GHz, 867Mbps 5GHz
- Easy Remote Management, TR-069 protocol enables an operator to remotely configure and manage end-user devices
- 4 external antennas provide stable wireless connections and optimal coverage
- Supports USB 2.0 port, easily share files & media with networked devices
- Full Gigabit Ports, Support 1000Mbps WAN port and four 1000Mbps LAN port, for ultrafast data transfer speeds

HARDWARE FEATURES

Interface	4 10/100Mbps LAN Ports 1 10/100Mbps WAN Port 1 USB 2.0 Port
Power Supply	12VDC/1.0A
Dimensions (W x D x H)	230.0 * 144.0 * 37.0 mm
Antenna Type	4 Fixed antennas

WIRELESS FEATURES

Wireless Standards	IEEE 802.11n/g/b 2.4GHz IEEE 802.11ac/n/a 5GHz
Frequency	2.4GHz and 5GHz
Signal Rate	2.4GHz: Up to 300Mbps 5GHz: Up to 867Mbps
Reception Sensitivity	5GHz: 11a 54M: -73dBm; 11ac VHT20 MCS8: -66dBm; 11ac VHT40 MCS9: -61dBm; 11ac VHT80 MCS9: -58dBm. 2.4GHz: 11g 54M: -75dBm; 11n HT20 MCS7: -73dBm; 11n HT40 MCS7: -70dBm
Transmit Power	CE: <20dBm(2.4GHz), <23dBm(5GHz) FCC: <30dBm
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	Provides WPA/WPA2 and WPA-PSK/WPA2-PSK authentication and TKIP/AES encryption security Provides 64/128-bit WEP encryption security and wireless LAN ACL (Access Control List).

SOFTWARE FEATURES

Quality of Service	WMM, Bandwidth Control
WAN Type	Dynamic IP, Static IP, PPPoE
Management	Access Control, Local Management, Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, NO-IP

SOFTWARE FEATURES

Access Control	Parental Control, Local Management Control, Host list, Access Schedule, Rule Management
Protocols	IPv4 and IPv6

OTHERS

Package Contents	AC1200 Wireless Dual Band Gigabit Router Power Adapter Quick Installation Guide RJ45 Cable
System Requirements	Microsoft Windows 10/8.1/8/7/Vista/XP/2000/NT/98SE, MAC OS, NetWare, UNIX or Linux
Environment	Operating Temperature: 0°C~40 °C (32 °F~104°F) Storage Temperature: -40°C~70 °C (-40 °F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Certifications	CE, FCC, RoHS

Company	Products	Content
About us	Home Wi-Fi System	Events
Contact us	Wi-Fi Router	Insights
	xDSL	
	GPON	
	G.fast	
	Range Extender	
	LTE	

